

# FCX2000 SERIES

# GRAPHIC BLADES

	<b>CB09UB</b>	<b>Angle 45° Diameter 0.9mm</b>	Standard blade for vinyl cutting & self-adhesive marking film (PVC film) up to 0.25 mm thick. Maximum cutting distance is approx. 13,123 ft.
	<b>CB09UB-K60</b>	<b>Angle 30° Diameter 0.9mm</b>	Supersteel Blade for cutting the window tint film or thin film, up to 0.25 mm thick.
	<b>CB15U</b>	<b>Angle 45° Diameter 1.5mm</b>	Supersteel blade for cutting rigid or thicker media, 0.25 mm to 0.5 mm thick. (laminates, smart device, device screen protection media)
	<b>CB15U-K30</b>	<b>Angle 60° Diameter 1.5mm</b>	Supersteel Blade for cutting rigid media, 0.25 mm to 0.5 mm thick. And also small detailed characters on marking film (up to 0.25mm). Recommended blade for sandblast rubber resist media cutting and Avery Series of Reflective sheeting.
	<b>CB15UA</b>	<b>Angle 45° Diameter 1.5mm</b>	Supersteel Blade for cutting high-intensity reflective film or harder film.
	<b>CB15UA-K30</b>	<b>Angle 60° Diameter 1.5mm</b>	Supersteel Blade for cutting rigid media, 0.25 mm to 0.5 mm thick. And also small detailed characters on marking film (up to 0.25mm). Recommended blade for sandblast rubber resist media cutting and Avery Series of Reflective sheeting.
	<b>PM-CB-001</b>	<b>Angle 60° Diameter 3mm</b>	Supersteel blade for cutting thick rigid materials such as corrugated paper up to E flute or chip board up to 2 mm thick.
	<b>CB30UC</b>	<b>Angle 45° Diameter 3mm</b>	Super steel blade for cutting thick rigid material such as cardstock and chip board up to 2mm

# FCX2000 SERIES









# GRAPHIC BLADE HOLDERS

	<b>PHP33-CB09N-HS</b> SPRING BUILT-IN	Compatible with Blades: <b>CB09UA • CB09UA-K60 • CB09UB • CB09UB-K60</b> 0.9mm, blue top, black ABS tip. Not recommended for CB09UA blades with springs.
	<b>PHP33-CB15N-HS</b> SPRING BUILT-IN	Compatible with Blades: <b>CB15U • CB15U-K30* • CB15UA</b> <b>CB15U-K20-2SP • CB15UA-K30 • CB15UB</b> 1.5mm**, red top, black ABS tip.
	<b>PHP35-CB09-HS</b> SPRING BUILT-IN	Compatible with Blades: <b>CB09UA • CB09UA-K60 • CB09UB • CB09UB-K60</b> 0.9mm, blue top, black brass tip.
	<b>PHP35-CB15-HS</b> SPRING BUILT-IN	Compatible with Blades: <b>CB15U • CB15U-K30* • CB15UA • CB15U-K20-2SP • CB15UA-K30 • CB15UB</b> 1.5mm**, red top, black brass tip. These brass tip blade-holders/plungers are more rigid & lend to more accurate cutting.
	<b>PHP34-BALL</b>	Ballpoint pen holder for black, oil based pen
	<b>PM-CH-001</b>	Compatible with Blades: <b>CB30UC-1 • PM-CB-001</b>
	<b>PHP71-SHARPIE</b>	Sharpie Pen holder with a metal sleeve that can be used with our FC & CE Cutters

**Recommended Setting On Control Panel for Small Detailed Figure and Character Cutting:**  
CB15U-K30 Offset +2, Force 10-14, Speed 30 or less, Acceleration 3

# FCX2000 SERIES

# GRAPHIC CREASING TOOLS

	<b>CP-001</b> 	Stick Type Creasing Tool for heavy paper
	<b>CP-002</b> 	Roller Type Creasing Tool for cardboard
	<b>CP-003</b> 	Roller Type Creasing Tool for corrugated board
	<b>PM-CT-002</b> 	Pen Type Creasing Tool for curves on heavy paper